

SUPER TYPHOON™ 12150 (WITH HOLE OUTLET)

FLOW RATE (L/H)	DISTANCE BETWEEN DRIPPERS (M)													
	0.15	0.20	0.25	0.30	0.35	0.40	0.50	0.60	0.65	0.70	0.75	0.80	0.90	1.00
0.80														
1.05		003880		004160										
1.65														
2.70														
Carton coils length (m)	1400	1400	1400	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500
Price (€)		128.7		121.79										

Missing catalog numbers available upon request.

SUPER TYPHOON™ 12150 ID11.8 KD 0.25 Inlet pressure 1.5 Bar

NOMINAL FLOW RATE 0.80 L/H.	SLOPE	DISTANCE BETWEEN DRIPPERS (M)						
		0.20	0.30	0.40	0.50	0.60	0.70	0.80
Uphill	2%	62	79	91	102	109	116	122
	1%	68	89	106	121	133	145	156
Flat terrain	0	73	99	122	142	161	179	196
	-1%	77	107	134	160	184	208	230
Downhill	-2%	82	116	148	180	210	240	270

NOMINAL FLOW RATE 1.05 L/H.	SLOPE	DISTANCE BETWEEN DRIPPERS (M)						
		0.20	0.30	0.40	0.50	0.60	0.70	0.80
Uphill	2%	53	69	80	91	98	105	111
	1%	57	76	91	104	116	127	136
Flat terrain	0	61	83	102	119	136	151	165
	-1%	64	89	110	132	151	170	189
Downhill	-2%	68	95	121	146	169	193	216

NOMINAL FLOW RATE 1.65 L/H.	SLOPE	DISTANCE BETWEEN DRIPPERS (M)						
		0.20	0.30	0.40	0.50	0.60	0.70	0.80
Uphill	2%	39	50	60	68	74	80	85
	1%	41	55	66	76	85	93	100
Flat terrain	0	44	59	72	85	96	106	117
	-1%	46	63	78	93	107	120	133
Downhill	-2%	48	67	84	101	117	132	148

NOMINAL FLOW RATE 2.70 L/H.	SLOPE	DISTANCE BETWEEN DRIPPERS (M)						
		0.20	0.30	0.40	0.50	0.60	0.70	0.80
Uphill	2%	29	38	46	53	58	64	68
	1%	30	41	49	57	64	71	77
Flat terrain	0	32	43	53	62	70	78	86
	-1%	33	45	56	67	76	85	94
Downhill	-2%	34	47	59	71	82	92	102

Max. lateral length (meters) at different slopes - 10% flow variation