

## SUPER TYPHOON™ 16100 (WITHFLAP OUTLET)

FLOW RATE (L/H)	DISTANCE BETWEEN DRIPPERS (M)													
	0.15	0.20	0.25	0.30	0.35	0.40	0.50	0.60	0.65	0.70	0.75	0.80	0.90	1.00
0.80		001920		001950		001970	001980	001990						
1.10		004200	004260	004350	004500	004700	004720	004760						
1.60		009000		009400	009470	009600	009800	009820						
2.70				011800		011850	011950	012110						
Carton coils length (m)	1800	1800	1800	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000
Price (€)		252.72	241.65	236.39	230.52	135.74	219.96	215.85			211.74	210.74		207.63

Missing catalog numbers available upon request.

## SUPER TYPHOON™ 16100 (WITHHOLE OUTLET)

FLOW RATE (L/H)	DISTANCE BETWEEN DRIPPERS (M)													
	0.15	0.20	0.25	0.30	0.35	0.40	0.50	0.60	0.65	0.70	0.75	0.80	0.90	1.00
0.80														
1.10		002100		002500	002700		003100	003260						
1.60	005000	005300	005600	005905			007000	007300			007600	007900		008200
2.70			009960	010100		010400	010600	010750						
Carton coils length (m)	1800	1800	1800	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000
Price (€)		151.71	145.07	141.90	138.39		239.09	129.57			127.11	126.51		124.64

Missing catalog numbers available upon request.

## SUPER TYPHOON™ 16100 ID16.2 KD 0.1 Inlet pressure 1.2 Bar

NOMINAL FLOW RATE 0.80 L/H.	SLOPE	DISTANCE BETWEEN DRIPPERS (M)						
		0.20	0.30	0.40	0.50	0.60	0.70	0.80
Uphill	2%	88	103	111	118	121	124	126
	1%	108	134	154	170	182	194	202
Flat terrain	0	131	174	212	247	278	308	337
	-1%	150	209	264	319	371	424	477
Downhill	-2%	171	248	324	403	493	583	673

NOMINAL FLOW RATE 1.10 L/H.	SLOPE	DISTANCE BETWEEN DRIPPERS (M)						
		0.20	0.30	0.40	0.50	0.60	0.70	0.80
Uphill	2%	78	93	102	109	114	118	121
	1%	91	116	134	149	161	173	182
Flat terrain	0	107	142	173	201	227	251	275
	-1%	119	164	207	249	289	328	366
Downhill	-2%	133	190	246	303	359	416	473

NOMINAL FLOW RATE 1.60 L/H.	SLOPE	DISTANCE BETWEEN DRIPPERS (M)						
		0.20	0.30	0.40	0.50	0.60	0.70	0.80
Uphill	2%	61	74	83	90	94	98	102
	1%	70	89	104	117	128	137	145
Flat terrain	0	80	106	129	151	170	188	206
	-1%	89	122	153	183	211	239	266
Downhill	-2%	98	138	177	216	254	293	331

NOMINAL FLOW RATE 2.70 L/H.	SLOPE	DISTANCE BETWEEN DRIPPERS (M)						
		0.20	0.30	0.40	0.50	0.60	0.70	0.80
Uphill	2%	47	59	68	75	80	85	89
	1%	52	67	80	90	100	108	115
Flat terrain	0	57	76	92	108	122	135	147
	-1%	62	84	105	125	143	161	178
Downhill	-2%	66	92	117	141	164	188	210

Max. lateral length (meters) at different slopes - 10% flow variation