

SUPER TYPHOON™ 16125 (WITHFLAP OUTLET)

FLOW RATE (L/H)	DISTANCE BETWEEN DRIPPERS (M)													
	0.15	0.20	0.25	0.30	0.35	0.40	0.50	0.60	0.65	0.70	0.75	0.80	0.90	1.00
0.80		001510		001517		001535	001570	001580						
1.10		004200		004600	004800	005000	005200	005220				005255	005275	
1.60	008300	008500		008900	009060	009300	009700	009900						
2.70								012550			012750			013550
Carton coils length (m)	1250	1250	1250	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500
Price (€)	238.94	203.22	192.30	211.79	203.33	199.97	195.26	192.15			188.99	188.19		

SUPER TYPHOON™ 16125 (WITHHOLE OUTLET)

FLOW RATE (L/H)	DISTANCE BETWEEN DRIPPERS (M)													
	0.15	0.20	0.25	0.30	0.35	0.40	0.50	0.60	0.65	0.70	0.75	0.80	0.90	1.00
0.80		001080	001097	001150										
1.10	001650	001800		002200	002400	002600	003000	003200				003600		
1.60	005600	006000	006200	006400	006600	006800	007300	007500			007700			
2.70		010200		010700										
Carton coils length (m)	1250	1250	1250	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500
Price (€)	143.45	122.00	115.44	127.14	122.06	120.05	117.21	115.35			113.45	112.97		

SUPER TYPHOON™ 16125 ID16.2 KD0.1 Inlet pressure 1.2 Bar

NOMINAL FLOW RATE 0.80 L/H.	SLOPE	DISTANCE BETWEEN DRIPPERS (M)							
		0.20	0.30	0.40	0.50	0.60	0.70	0.80	
Uphill	2%	88	103	111	118	121	124	126	
	1%	108	134	154	170	182	194	202	
Flat terrain	0	131	174	212	247	278	308	337	
	-1%	150	209	264	319	371	424	477	
Downhill	-2%	171	248	324	403	493	582	666	

NOMINAL FLOW RATE 1.10 L/H.	SLOPE	DISTANCE BETWEEN DRIPPERS (M)							
		0.20	0.30	0.40	0.50	0.60	0.70	0.80	
Uphill	2%	78	93	102	109	114	118	121	
	1%	91	116	134	149	161	173	182	
Flat terrain	0	107	142	173	201	227	251	275	
	-1%	119	164	207	249	289	328	366	
Downhill	-2%	133	190	246	303	359	416	471	

NOMINAL FLOW RATE 1.60 L/H.	SLOPE	DISTANCE BETWEEN DRIPPERS (M)							
		0.20	0.30	0.40	0.50	0.60	0.70	0.80	
Uphill	2%	61	74	83	90	94	98	102	
	1%	70	89	104	117	128	137	145	
Flat terrain	0	80	106	129	151	170	188	206	
	-1%	89	122	153	183	211	239	266	
Downhill	-2%	98	138	177	216	254	293	331	

NOMINAL FLOW RATE 2.70 L/H.	SLOPE	DISTANCE BETWEEN DRIPPERS (M)							
		0.20	0.30	0.40	0.50	0.60	0.70	0.80	
Uphill	2%	47	59	68	75	80	85	89	
	1%	52	67	80	90	100	108	115	
Flat terrain	0	57	76	92	108	122	135	147	
	-1%	62	84	105	125	143	161	178	
Downhill	-2%	66	92	117	141	164	188	210	

Max. lateral length (meters) at different slopes - 10% flow variation