

## SUPER TYPHOON™ 16150 (WITHFLAP OUTLET)

FLOW RATE (L/H)	DISTANCE BETWEEN DRIPPERS (M)													
	0.15	0.20	0.25	0.30	0.35	0.40	0.50	0.60	0.65	0.70	0.75	0.80	0.90	1.00
0.80		001404		001420		001350	001360	001370						
1.10			002550	002700	002770	002810	002815	002817		002825				002840
1.60				005400	005450	005600	005660	005670	005672	005674	005680	005683		005690
2.70				010050		010150	010250							
Carton coils length (m)	1150	1150	1150	1250	1250	1250	1250	1250	1250	1250	1250	1250	1250	1250
Price (€)	227.87	208.49	201.36	201.47	197.85	195.05	191.19	188.64			186.09			183.53

## SUPER TYPHOON™ 16150 (WITHHOLE OUTLET)

FLOW RATE (L/H)	DISTANCE BETWEEN DRIPPERS (M)													
	0.15	0.20	0.25	0.30	0.35	0.40	0.50	0.60	0.65	0.70	0.75	0.80	0.90	1.00
0.80	001030		001170											
1.10	001427	001435	001465	001600	001800	002000	002140	002220	002230	002240				
1.60		002970		003400	003700	003900	004100	004300	004340	004380	004500			004900
2.70				005770		005790	005850							
Carton coils length (m)	1150	1150	1150	1250	1250	1250	1250	1250	1250	1250	1250	1250	1250	1250
Price (€)	138.63	125.15	120.89	120.95	118.74	117.09	114.78	113.24			111.71			110.18

## SUPER TYPHOON™ 16150 ID16.2 KD 0.1 Inlet pressure 1.5 Bar

NOMINAL FLOW RATE 0.80 L/H.	SLOPE	DISTANCE BETWEEN DRIPPERS (M)						
		0.20	0.30	0.40	0.50	0.60	0.70	0.80
Uphill	2%	97	116	128	137	142	147	151
	1%	114	144	167	186	202	215	226
Flat terrain	0	133	176	215	250	283	314	342
	-1%	148	205	258	309	358	407	455
Downhill	-2%	165	236	306	376	446	517	195

NOMINAL FLOW RATE 1.05 L/H.	SLOPE	DISTANCE BETWEEN DRIPPERS (M)						
		0.20	0.30	0.40	0.50	0.60	0.70	0.80
Uphill	2%	86	104	117	127	133	139	144
	1%	98	125	146	164	179	193	204
Flat terrain	0	111	148	181	211	238	263	287
	-1%	122	168	210	251	290	328	366
Downhill	-2%	134	190	244	297	350	403	457

NOMINAL FLOW RATE 1.65 L/H.	SLOPE	DISTANCE BETWEEN DRIPPERS (M)						
		0.20	0.30	0.40	0.50	0.60	0.70	0.80
Uphill	2%	64	79	90	99	106	111	116
	1%	71	92	108	123	134	146	155
Flat terrain	0	79	105	128	149	169	187	204
	-1%	86	118	147	175	202	227	252
Downhill	-2%	93	130	166	200	234	268	302

NOMINAL FLOW RATE 2.70 L/H.	SLOPE	DISTANCE BETWEEN DRIPPERS (M)						
		0.20	0.30	0.40	0.50	0.60	0.70	0.80
Uphill	2%	49	63	73	81	88	94	99
	1%	53	69	83	95	104	114	122
Flat terrain	0	57	77	94	109	123	137	149
	-1%	62	84	104	123	141	158	175
Downhill	-2%	65	90	114	136	158	179	200

Max. lateral length (meters) at different slopes - 10% flow variation