

## SUPER TYPHOON™ 16200 (WITHFLAP OUTLET)

FLOW RATE (L/H)	DISTANCE BETWEEN DRIPPERS (M)													
	0.15	0.20	0.25	0.30	0.35	0.40	0.50	0.60	0.65	0.70	0.75	0.80	0.90	1.00
1.20		001100	001170	001400	001600	001800	002080							002160
1.80	002700	003100		004100	004480	004800	005200	005400		005550	005700	005900		
2.75			007400	007700	008000			008750				009200		
Carton coils length (m)	1000	1000	1000	1250	1250	1250	1250	1250	1250	1250	1250	1250	1250	1250
Price (€)	143.15	131.84		149.10	146.84	145.16	142.77	141.18			138.99	139.32		138.03

## SUPER TYPHOON™ 16200 ID15.5 KD0.1 Inlet pressure 1.5 Bar

NOMINAL FLOW RATE 1.20 L/H.	SLOPE	DISTANCE BETWEEN DRIPPERS (M)						
		0.20	0.30	0.40	0.50	0.60	0.70	0.80
Uphill	2%	73	91	103	113	121	127	133
	1%	82	105	124	140	154	166	177
Flat terrain	0	90	120	147	171	193	214	234
	-1%	97	133	166	197	226	256	284
Downhill	-2%	105	147	187	227	265	303	342

NOMINAL FLOW RATE 1.80 L/H.	SLOPE	DISTANCE BETWEEN DRIPPERS (M)						
		0.20	0.30	0.40	0.50	0.60	0.70	0.80
Uphill	2%	56	70	81	90	97	102	107
	1%	61	80	94	107	118	128	138
Flat terrain	0	67	89	109	127	143	158	173
	-1%	72	99	123	145	167	188	208
Downhill	-2%	77	107	136	163	190	216	242

NOMINAL FLOW RATE 2.75 L/H.	SLOPE	DISTANCE BETWEEN DRIPPERS (M)						
		0.20	0.30	0.40	0.50	0.60	0.70	0.80
Uphill	2%	46	59	68	77	83	89	94
	1%	49	64	77	88	97	106	114
Flat terrain	0	53	71	86	100	113	125	137
	-1%	56	77	95	112	128	144	158
Downhill	-2%	59	82	103	123	142	161	180

Max. lateral length (meters) at different slopes - 10% flow variation