

SUPER TYPHOON™ 16250 (WITHHOLE OUTLET)

FLOW RATE (L/H)	DISTANCE BETWEEN DRIPPERS (M)													
	0.15	0.20	0.25	0.30	0.35	0.40	0.50	0.60	0.65	0.70	0.75	0.80	0.90	1.00
1.20	001100	001350		001700	002100	002300	002500	002650			002750			
1.80		003300	003600	003900	004300	004500	004900	005300			005600	005800	006000	006200
2.75	007000	007300	007500	007700		008200	008600	008800		009000	009200		009600	
Carton coils length (m)	800	800	800	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000

SUPER TYPHOON™ 16250 ID 15.5 KD 0.1 Inlet pressure 1.5 Bar

NOMINAL FLOW RATE 1.20 L/H.	SLOPE	DISTANCE BETWEEN DRIPPERS (M)						
		0.20	0.30	0.40	0.50	0.60	0.70	0.80
Uphill	2%	73	91	103	113	121	127	133
	1%	82	105	124	140	154	166	177
Flat terrain	0	90	120	147	171	193	214	234
	-1%	97	133	166	197	226	256	284
Downhill	-2%	105	147	187	227	265	303	342

NOMINAL FLOW RATE 1.80 L/H.	SLOPE	DISTANCE BETWEEN DRIPPERS (M)						
		0.20	0.30	0.40	0.50	0.60	0.70	0.80
Uphill	2%	56	70	81	90	97	102	107
	1%	61	80	94	107	118	128	138
Flat terrain	0	67	89	109	127	143	158	173
	-1%	72	99	123	145	167	188	208
Downhill	-2%	77	107	136	163	190	216	242

NOMINAL FLOW RATE 2.75 L/H.	SLOPE	DISTANCE BETWEEN DRIPPERS (M)						
		0.20	0.30	0.40	0.50	0.60	0.70	0.80
Uphill	2%	46	59	68	77	83	89	94
	1%	49	64	77	88	97	106	114
Flat terrain	0	53	71	86	100	113	125	137
	-1%	56	77	95	112	128	144	158
Downhill	-2%	59	82	103	123	142	161	180

Max. lateral length (meters) at different slopes - 10% flow variation