LX SERIES

SPRAY HEADS & NOZZLES

Weathermatic™
Water Conserving Innovation



1 FUNCTIONAL FLUSH PLUG

- Easy lift, flexible material allows you to quickly pop off flush plug without having to unscrew
- Lift the turret for nozzling so you can save time (and your pinky!)

2 SURE GRIP CAP

- Wet or muddy-hand friendly
- Available non-potable cover fits snugly on cap for reclaimed water usage

3 SUPERIOR SEAL

- 10-year rated; exceeds 11,000 cycles in sand burial tests
- One piece seal design prevents cap to body leaks
- Ultra-low flushing design enables pop-up & sealing at only 5 psi and allows more heads to be installed on a line
- Extra long wiper seal design provides extended life and positive retraction in the toughest conditions

4 RUGGED RATCHET

- Beefy two piece ratchet teeth provide just the right feel; not too light where the head could inadvertently move the arc, not too tight where you can't adjust under pressure
- Try one and compare!

5 READY CHECK™ CHECK VALVE

- Prevent low head drainage by purchasing the affordable LX-CV models
- With the ability to hold back 9 1/2' of elevated water (ft/head), the LX-CV brings the industry an economical way to conserve water lost to low head drainage
- Combine the LX-CV with the standard Ready Check™ check valve on the Weathermatic Turbo rotor line for a totally checked water conserving system

6 SUPERIOR MATERIAL

- Weathermatic uses only 100% virgin material – no regrind
- For added strength: eight internal reinforcements and a ribbed body

7 LX MPR NOZZLES

- Excellent edge-to-edge watering and performance
- Consistent patterns across each nozzle in the bag
- Color-coded identification in a resealable bag



8 LX ADJUSTABLE NOZZLES

- The ultimate nozzle for flexibility in the field and reducing nozzle inventories
- Arcs are easily adjusted by hand using sure-grip ridges or by coin/ screwdriver in slot
- Color-coded identification in a resealable bag

9 LX B SERIES BRASS NOZZLES

- The best performing spray nozzle in the business, period.
- Wide nozzle radius selection 3', 10', 12', 15', 18', 20' and 24', plus strip nozzles



- Extended spacing gets the job done with fewer heads and less cost by saving pipe, wire, fittings, and labor

Specification Guide	
Model	**Description**
LX3	3" pop-up height
LX4	4" pop-up height
LX6	6" pop-up height
LX12	12" pop-up height

Copyright 2013 Weathermatic. All Rights Reserved AD4005_revA

weathermatic.com